



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 15 FloInducer Improves Flow & Leveling

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Improves Flow & Leveling Characteristics	Solvent	Immediately Effective	1 - 2% of Total Weight	

PERFORMANCE

RAYBO 15 can be used effectively to improve flow and leveling in coatings which resist flow. It is effective whether flow resistance results from high vehicle solids, high pigment load, or high oil demand. Most effective when used with long oil alkyds and oil based products.

RAYBO 15 is particularly useful for improving flow and leveling in coatings primarily intended for brush or roller application.

The use of RAYBO 15 can improve durability and flexibility of the coating.

ADVANTAGES

- Effective Immediately
- Can be post added

RECOMMENDATIONS For Flow and Leveling – 1 – 2% of Total Weight
Can be added at any time including post addition.

PHYSICAL DATA** Weight/Gallon8.4 – 8.6 lbs
Consistency.....Paste

CONTAINER SIZES North America: 5 gal. pail*, 55 gal. drum, and bulk.
Global Zones: 5 gal. pail*, 55 gal. drum.

20100104

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

