



TECHNICAL BULLETIN

Raybo Chemical Company

TELEPHONE: 304-525-5171

RAYBO 62 HydroFlo Flow Control Agent

REFERENCE	FEATURES	SYSTEM	COMMENTS	USAGE (%)	REFERENCE
	Flow Control	Water & Water Reducible	No Intercoat Problems	0.3 - 1% of Total Weight	

PERFORMANCE

RAYBO 62 is an easy to use, effective flow control agent for water and water reducible systems. Even at very low concentrations it is effective in preventing crawling, creeping, and edge effects. Water reducible coatings are often thinned, by the user, to low viscosities for use in dip or spray applications. The use of RAYBO 62 will allow thinning of water reducible coatings without accompanying film defects. Its use produces a more forgiving film with more even flow out when thinned.

RAYBO 62 can be used without fear of intercoat adhesion loss or reduced gloss making it useful in both primers and topcoat formulations.

ADVANTAGES

- Flow control without intercoat adhesion loss
- Can be used in primer and topcoat formulations
- Effective at low concentrations

RECOMMENDATIONS For Flow Control – 0.3 – 1% of Total Weight

Can be added at any point after resin solubilization including post addition.

PHYSICAL DATA**

Weight/Gallon8.36 lbs
 pH.....10.0 ± 1.0
 Appearance.....Water White Liquid

CONTAINER SIZES

North America: 5 gal. pail*, 55 gal. drum, and bulk.
 Global Zones: 5 gal. pail*, 55 gal. drum.

20100706

* One gallon containers available upon request.

** Typical Properties; not sales specifications.

The information and data stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.

