

## **Raybo Chemical Company**

## TELEPHONE: 304-525-5171

## **RAYBO 85 Rustib**

## **Resists Corrosion Undercutting**

R	FEATURES	SYSTEM	COMMENTS	USAGE (%)	R	
G U I D E R E N C E	Resists Corrosion Undercutting of Paint	Solvent	Cationic	0.5% of Solids	E F E R E N C E	
<b>PERFORMANCE</b> RAYBO 85 is a cationic wetting agent. Because of its polarity, it is attracted to the metal surface forming a mono-molecular hydrophobic layer. This affinity increases adhesion and resistance to corrosion undercutting in coatings containing RAYBO 85.When added to coatings pigmented with transition metals containing pigments like phthalocyanine blue, insure that the surfactant demand has been met. If it has not, RAYBO 85 will be absorbed onto the pigment, reducing corrosion protection.						
ADVANTAGES		<ul> <li>Polar bonding with metal surface for increased corrosion resistance.</li> <li>Listed with USDA</li> </ul>				
<b>RECOMMENDATIONS</b> For corrosion Resistance – 0.5% of Total Solids Post addition recommended						
Consistency		on ′	Paste			
CONTAINER S	Global Zone	ca: 5 gal. pail*, 55 ga s: 5 gal. pail*, 55 ga	al. drum.		20100104	
* One gallon containers available upon request. ** Typical Properties; not sales specifications.						

The information and date stated herein, although in no way guaranteed, are based upon tests and reports considered to be reliable and are believed to be accurate. No warranty either expressed or implied, is made or intended. Use by customer should be based upon its own investigations and appraisals. Any recommendation should not be construed as an invitation to use a material in infringement of patents.



Performance Additives Department Huntington, WV 25721 Tel: 304-525-5171 Fax: 304-525-2921 U.S. Marketing Division Raybo Chemical Company Huntington, WV 25721 Tel: 304-525-5172 Fax: 304-525-2921



Exclusive Export Management Company W.R. Magnus, Inc. Tel.: 301-263-6124 Email: rwmagnus@cocexport.com



Global Dist Zones:

Representatives in 31 Countries